

DMG80480T070_09WTR


Features:

- Based on T5L0, running DGUS II system, industrial grade.
- 7.0-inch, 800*480 pixels resolution, 262K colors, TN-TFT-LCD, normal viewing angle.
- Resistive touch screen.
- Highlight 720nit.
- Anti-UV, with conformal coating.



1. Hardware and interface

1.1 Hardware interface



Hardware interface

1.2 Interface description

| No. | Name | Description |
|-----|---------------------------|---|
| 1 | T5L0 ASIC | Developed by DWIN in 2020. 1MBytes Nor Flash on the chip, 512Kbytes storage for the user database. Rewrite cycle > 100,000 times |
| 2 | LCM interface | FPC50_0.5mm, RGB interface |
| 3 | RTP interface | 4Pin_1.0mm interface |
| 4 | User interface | 8Pin_2.0mm socket for power supply and serial communication. Download rate(typical value): 12KByte/s |
| 5 | Flash | 16MBytes NOR Flash, for fonts, pictures and audio files. Rewrite cycle: over 100,000 times |
| 6 | Expand Flash | Expandable to 48Mbytes NOR Flash or 32Mbytes NOR Flash+512Mbytes NAND Flash |
| 7 | Buzzer | 3V passive buzzer. Power: <1W |
| 8 | RTC | Super-capacitor for power supply. Accuracy: $\pm 20\text{ppm}$ @25 °C . It can work normally for 30 days after power failure |
| 9 | SD card slot | The SD card should be formatted as FAT32 file system. Download files by SD interface can be displayed in statistics. Download rate: 4Mb/s |
| 10 | Reserved module interface | Wi-Fi module: connect to the cloud platform to update remotely USB module: download files by USB flash disk |
| 11 | PGT05 interface | When product crashes by accident, you can use PGT05 to update DGUS kernel and make the product return to normal |

2.Specification parameters

2.1 Display parameters

| | |
|---|---|
| LCD Type | TN, TFT LCD |
| Viewing Angle | Normal viewing angle, 70°/70°/50°/70° (L/R/U/D) |
| Resolution | 800×480 pixels (support 0°/90°/180°/270°) |
| Color | 18-bit 6R6G6B |
| Active Area (A.A.) | 154.08mm (W)×85.92mm (H) |
| Visual Area (V.A.) | - |
| Backlight | LED |
| Backlight Lifetime | >30000 hours (Time of the brightness decaying to 50% on the condition of continuous working with the maximum brightness) |
| Brightness | 720nit |
| Brightness Control | 0~100 grade (When the brightness is adjusted to 1%~30% of the maximum brightness, flickering may occur and is not recommended to use in this range) |
| Note: Long time display of high contrast still image over 30 minutes may lead to display residual shadow, please use screen saver to avoid this problem. | |

2.2 Touch parameters

| | |
|---------------------|------------------------------|
| Type | RTP (Resistive touch panel) |
| Structure | ITO film + ITO glass |
| Touch Mode | Support point touch and drag |
| Surface Hardness | 3H |
| Light Transmittance | Over 80% |
| Life | Over 1,000,000 times touch |

2.3 Serial interface parameters

| | | | | | |
|-----------------|---|-----|-----|-----|------|
| Mode | UART2: ON=TTL/CMOS; OFF=RS232 UART4: ON=TTL/CMOS; OFF=RS232(Only available after OS configuration) | | | | |
| Voltage Level | Test Condition | Min | Typ | Max | Unit |
| | Output 1, Iout = 1mA | 3.0 | 3.3 | - | V |
| | Output 0, Iout = -1mA | - | 0 | 0.3 | V |
| | Input 1, Iin = 1mA | 2.4 | 3.3 | 5.0 | V |
| | Input 0, Iin = -1mA | 0 | - | 0.5 | V |
| Baud Rate | 3150~3225600bps, typical value of 115200bps | | | | |
| Data Format | UART2: N81 UART4: N81/E81/O81/N82 4 modes (OS configuration) | | | | |
| Interface Cable | 8Pin_2.0mm | | | | |

2.4 Electrical specifications

| | | |
|-------------------------------------|-----------------------------|------------------------|
| Rated Power | <5W | |
| Operating Voltage | 6~36V, typical value of 12V | |
| Operating Current | 240mA | VCC=12V, max backlight |
| | 80mA | VCC=12V, backlight off |
| Recommended power supply: 12V 1A DC | | |

2.5 Operating environment

| | |
|-----------------------|------------------------------------|
| Operating Temperature | -20℃~70℃ (12V @ 60% RH) |
| Storage Temperature | -30℃~80℃ |
| Conformal coating | Yes |
| Operating Humidity | 10%~90%RH, typical value of 60% RH |

3. Reliability test

3.1 Electrostatic discharge test

Test temperature: 25°C. Test humidity: 50%RH.

Test process: the product was placed on the test bench to perform contact and air discharge in turn of the serial screen iron frame and display area as shown in Fig.3.1 below. During the experimental process, it was observed whether the screen is dead, black, white, splash, or reboot. According to the experiment results, the performance is in line with the criteria GB/T 17626.2 B level and above.



3.1 Electrostatic discharge test

| Discharge Type | Discharge Value | Result |
|-------------------|-----------------|------------------|
| Contact discharge | ±6KV | Normal operation |
| Air discharge | ±8KV | Normal operation |

3.2 EFT test

Test temperature: 25°C. Test humidity: 50%RH.

Test process: the product was placed on the test bench to perform contact and the smart screen is energized by the power supply coupled with a EFT generator as shown in Fig. 3.2 below. During the experimental process, it was observed whether abnormal reset, display or touch phenomena occurs. According to the experiment results, the performance is in line with the criteria GB/T 17626.2 B level and above.





3.2 EFT test

| Test Item | Test Standard | Result |
|--------------|---------------|------------------|
| Power supply | ±2KV;100KHz | Normal operation |

4.Packaging & dimensions

| Form Factor | 190.5mm (W)×105.4mm (H)×16.4mm (T) | | | |
|-------------------------|---|-------|----------------|---------------|
| Installation Dimensions | Positioning hole: 166.0 (+0.3mm)×101.2 (+0.3mm) | | | |
| Net Weight | 265g | | | |
| Packaging Standards | | | | |
| Model | Dimensions | Layer | Quantity/Layer | Quantity(Pcs) |
| Carton1: | 220mm(L)×160mm(W)×47mm (H) | 1 | 1 | 1 |
| Carton2: | 250mm(L)×200mm(W)×80mm (H) | 2 | 1 | 2 |
| Carton3: | 320mm(L)×270mm(W)×80mm (H) | 2 | 2 | 4 |
| Carton4: | 435mm(L)×335mm(W)×290mm(H) | - | - | - |
| Carton5: | 600mm(L)×430mm(W)×290mm(H) | 1 | 40 | 40 |

Disclaimer: the data is for reference only and the information of product design that do not affect performance parameters and utilization is subject to alternation without prior notice.




| Definition | Pin# | Type | Description |
|------------|------|------|-------------|
| VIN | 1, 2 | P | Power Input |
| TX4 | 3 | O | Output |
| TX2 | 4 | O | Output |
| RX2 | 5 | I | Input |
| RX4 | 6 | I | Input |
| GND | 7, 8 | P | GND |

Location hole is used as position reference.
Unmarked Tolerance is +/-0.3mm
Active area is marked in Dash lines

| Model | DMG80480T070-09WTR | | | | DWIN Technologies | | | |
|---------|--------------------|----------|------|------|-------------------|--|--|--|
| Drawing | A 4 | Drawn | DWIN | Date | | | | |
| Scale | 1:1 | Review | | Date | | | | |
| Unit | MM | Approval | | Date | | | | |

5 Debugging tools

It is recommended for new users of DWIN smart LCMs to purchase official accessories.
For more details, please refer to customer service center.



6 T5L series IC features

(1) Mature and stable 8051 core which is the most widely used with the maximum operating frequency of T5L is up to 250MHz, 1T(single instruction cycle) high speed operation.

(2) Separate GUI CPU Core running DGUS II System

- High-speed display memory, 2.4GB/S bandwidth.
- 2D hardware acceleration, the decompression speed of JPEG is up to 200fps@1280*800 and the UI with animation and icons as its main feature is extremely cool and smooth.
- Images and icons stored in JPEG format. Adopt Low-cost 16Mbytes SPI Flash.
- Support CTP or RTP with adjustable sensitivity and maximum 400 Hz touch frequency.
- way 15bit 32Ksps PWM digital power amplifier driver loudspeaker, save power amplifier cost and achieve high signal-to-noise ratio and sound quality restoration.
- 128Kbytes variable storage space for exchanging data with OS CPU Core and memory.
- Support development by DGUS V7.624 and simulation on PC. Support background remote upgrade.

(3) Separate CPU (OS CPU) core runs user 8051 code or DWIN OS system and user CPU is omitted in practical application:

- Standard 8051 architecture and instruction set, 64Kbytes code space, 32Kbytes on-chip RAM.
- 64 bit integer mathematical operation unit (MDU), including 64 bit MAC and 64 bit divider.
- 28 IOs, 4-channel UARTs, 1-channel CAN, up to 8-channel 12-bit A/Ds and 2-channel 16-bit PWM of adjustable resolution.
- Support IAP on-line simulation and debugging with unlimited number of breakpoints.
- Upgrade code online through DGUS system.

(4) 1Mbytes on-chip Flash with DWIN patent encryption technology ensure code and data security.

(5) Operating temperature ranges from -40℃ to +85℃ (IC operating temperature customizable from -55℃ to 105℃).

DWIN encourages users to design your own customized product based on T5L.

7.Revision records

| Rev | Revise Date | Content | Editor |
|-----|-------------|--|--------|
| 00 | 2021-09-25 | First Edition | ZYJ |
| 01 | 2022-01-05 | Update flash size, physical drawing and RTC accuracy description | ZYJ |

Please contact us if you have any questions about the use of this document or our products, or if you would like to know the latest information about our products.

E-mail: dwinhmi@dwin.com.cn

DWIN website: <http://forum.dwin.com.cn>

Thank you all for continuous support of DWIN, and your approval is the driving force of our progress!